

Model: SM20ES

ON DEMAND SEAL PLATE SIGNIFICANTLY REDUCES ENERGY CONSUMPTION



FEATURES

- Self-Regulating Boardless Square Rod for Increased Transversal Rigidity and Consistent Cutting
- NEW FILM CRADLE MOUNT: Saves Labor, Film Changeover is Fast and Easy with New Design; No Initial Set up or Assembly
- Fixed Distance Photoeye to Detect All Tray Colors
- Electronic Temperature Controlled Film Cut Off Rod
- NEW Circuit Breakers Replace Fuses for Fast and Easy Reset with Less Maintenance
- On-Demand Timer Controlled Heated Seal Plate That Significantly Reduces Power Consumption by 80%
- Seal Plate Reaches Seal Temperature Within Seconds
- Thermistor Controlled Circuit that Reduces Power Consumption as Residual Heat Increases in Seal Plate
- Dual Outlet Accessory Plug In with GFCI for Improved Circuit Integrity and Protection
- All Stainless Steel Fully Welded Construction
- Two Film Roll Capacity, 20" Maximum Roll Width, 8" Maximum Roll Diameter, Adjustable Film Tension
- Easy to Use Film Selector Feature
- Supplied With A Replaceable Non-Stick Cover to Maintain A Hygienic Seal Surface
- Adjustable, Oversized Stainless Steel Foot Pads for Easy Leveling on Uneven Floors
- Accessories to Fit Any Scale Model, Specify Scale Make
- Local Utility Rebates may be Available



Show with Optional Wings, Monitor Mounts and Label Dispenser

MODEL SPECS

MODEL	SM20ESC6
FILM MOUNT	NEW Cradle Mount
FILM CAPACITY	Two 20" Roll
SEAL PLATE	6" x 15"
OVERALL DIMENSIONS	25" D, 25" W, 37" H (64 D, 64 W, 94 H cm)
POWER	 115 Volt, 16 Amp, 1,840 Watts (Non Continuous), 60Hz 20A breaker, compatible with NEMA 5-20P (shown) 

OPTIONS

- 8" x 15" Seal Plate
- REINFORCED Right or Left Wings
- All Purpose Shelf
- Single or Double Post with Cord Guides
- Monitor Mount to Fit All Scales
- Printer Shelf
- Label Dispenser with Stand

